### Advantronic

## **CPR - DECLARATION of PERFORMANCE**

N° TU0210CPR (Conformity EU 305/2011)

1. Unique identification code of the product type:

#### ATW530A

#### **Advantronic Systems, SL**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under article 11(4) of the CPR:

# ATW530A BI-DIRECTIONAL WIRELESS ADDRESSABLE MULTICRITERIA DETECTOR WITH VARIABLE SENSITIVITY

Operating Frequency Band: 868 MHz; 916 MHz

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

### For use in compatible fire detection and alarm system

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under article 11(5):

ADVANTRONIC SYSTEMS SL C/ Yunque, 9 Nave B1 28760 – Tres Cantos – Madrid - Spain advantronic@advantronic.es www.advantronic.es

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in article 12(2):

#### N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

### System 1

7. In case of the declaration of performance concerning a construction product covered by harmonized standard:

EN 54-5:2000+A1:2002 EN 54-7:2000 + A1:2002+A2:2006 EN 54-25:2008 + AC :2012

IMQ S.p.A., N.B. No. 0051, performed the necessary initial inspection of the manufacturing plant and the factory production control together with ongoing continuous surveillance and issued the following certificates confirming constancy of the conformity of the factory production control

ATW530A

0051-CPR-2355

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

N/A

# **Advantronic**

### 9. Declared performance

ESSENTIAL CHARACTERISTICS	CLAUSE APPLICABLE	PERFORMANCE	HARMONISED STANDARD
Nominal activation conditions / Sensitivity, Response delay (response time) and Performance under fire conditions	4.2, 4.3, 5.2 to 5.6, 5.8, 6.2 (Suffix R)	PASS	EN 54-5:2000 +A1:2002
Operational reliability	4.4 to 4.11	PASS	
Tolerance to supply voltage	5.7	PASS	
Durability of operational reliability and	5.9, 5.10	PASS	
response delay; temperature resistance	,		
Durability of operational reliability;	5.14 to 5.17	PASS	
vibration resistance			
Durability of operational reliability;	5.11, 5.12	PASS	
humidity resistance	,		
Durability of operational reliability;	5.13	PASS	
corrosion resistance			
Durability of operational reliability;	5.18	PASS	
electrical stability			
		l L	
Nominal activation conditions / Sensitivity,	4.8, 5.2, 5.3, 5.4,	PASS	
Response delay (response time) and	5.6, 5.7, 5.18		
Performance under fire conditions			EN 54-7:2000+ A1:2002+A2:2006
Operational reliability	4.2 to 4.7, 4.9 to	PASS	
operational reliability	4.11		
Tolerance to supply voltage	5.5	PASS	
Durability of operational reliability and	5.8, 5.9	PASS	
response delay; temperature resistance			
Durability of operational reliability;	5.13 to 5.16	PASS	
vibration resistance			
Durability of operational reliability;	5.10, 5.11	PASS	
humidity resistance			
Durability of operational reliability;	5.12	PASS	
corrosion resistance			
Durability of operational reliability;	5.17	PASS	
electrical stability			
Performance parameters under fire	4.1, 4.2.2, 5.2,	PASS	
conditions	8.3.7		
Response delay (response time to fire)	8.2.3, 8.2.6	PASS	
Operational reliability	4.2.1, 4.2.3 to	PASS	
operational remarks	4.2.7, 5.3, 5.4, 6, 7,		
	8.2.2, 8.2.4, 8.2.5,		
	8.2.7, 8.2.8, 8.2.9,		
	8.3.1, 8.3.2, 8.3.3,		
N	8.3.4, 8.3.5, 8.3.6	DACC	EN 54-25:2008 + AC:2012
Durability of operational reliability,	8.3.9, 8.3.10, 8.3.11	PASS	
temperature resistance		DACC	
Durability of operational reliability, vibration	8.3.16, 8.3.17 to	PASS	
resistance	8.3.19	P.466	
Durability of operational reliability, humidity	8.3.13, 8.3.14	PASS	
resistance	22.15	F:55	
Durability of operational reliability,	8.3.15	PASS	c
corrosion resistance			
Durability of operational reliability,	8.3.20	PASS	
electrical stability			

## **Advantronic**

10. The performance of the products identified in points 1 and 2 are in conformity with the declared performance in the point 9. This declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Andrés Martínez – General Manager – Tres Cantos – Madrid - Spain

Tres Cantos, 01 April 2021

**Andrés Martínez** General Manager